

MED-W-OMNI

OMNIDIRECTIONAL MEDIUM INTENSITY STROBE (WHITE)



FEATURES

- Ideal for rural areas; no need to paint the tower, no need for red lights
- Light weight flash head
- Fingerprint protected flash tube
- No electronics in flash head
- 7.88" dia. bolt pattern. Available in 13¼" dia. bolt pattern

SPECIFICATIONS

Light output

Flash color	White
Intensity, day mode	20 000 cd ±25%
Intensity, night mode	2 000 cd ±25%
Horizontal coverage	360°
Vertical beam	3°
Expected min. lamp life	25 000 hours

Electrical value

Power consumption	130 Watts
Current (120V version)	4 A (rms)
Power requirements	120 Vac 50/60hz also available in 240 Vac and 24 Vdc




Mechanical

Flash head weight	3.6 Kg (8 lbs)
Controller weight	15 Kg (33 lbs)
Flash head dimensions	254 mm Ø x 490 mm high (10"Ø x 19¼" high)
Controller dimensions (W x H x D)	355 mm x 406 mm x 222 mm (14" x 16" x 8¾")

Others

FAA type	L-865
Transport Canada type	CL-865
Operating temperature	-55°C to 55°C (-67°F to 131°F)
Warranty	2 years

COMPLIANT WITH:

- **FAA** AC 150/5345-43F
-  SPE-1000
-  Transports Canada Transport Canada **CAR 621.19**
-  Industrie Canada Industrie Canada **ICES-003**
- **FC** PART 15