

# MED-W3R360

## WHITE/RED MEDIUM INTENSITY STROBE (WHITE/RED)



### FEATURES

- Specifically designed for mid-level applications
- 3 flash head system: 1 controller
- Ideal for urban areas
- Reduced energy consumption by 90% versus incandescent
- Real glass lens – no aging discoloration
- No electronics in flash head
- \* ice guard sold separately

### SPECIFICATIONS

#### Light output

Flash color	White and red
Intensity, day mode	20 000 cd $\pm$ 25%
Intensity, night mode	2 000 cd $\pm$ 25% (red)
Horizontal coverage	360°
Vertical beam	3°
Expected min. lamp life	40 000 hours

#### Electrical value

Power consumption	150 Watts
Current (120Vac version)	4 A (rms)
Power requirements	120 Vac 50/60hz also available in 240 Vac and 24 Vdc




#### Mechanical

Flash head weight	9.5 Kg (21 lbs)
Controller weight	15 Kg (33 lbs)
Flash heads dimensions (W x H x D)	395 mm x 450 mm x 170 mm (15½" x 17¾" x 6¾")
Controller dimensions (W x H x D)	355 mm x 406 mm x 222 mm (14" x 16" x 8¾")

#### Others

FAA type	L-865 / L-864
Transport Canada type	CL-865 / CL-864
Operating temperature	-55°C to 55°C (-67°F to 131°F)
Warranty	2 years

### COMPLIANT WITH:

- **FAA** AC 150/5345-43F
-  SPE-1000
-  Transports Canada Transport Canada **CAR 621.19**
-  Industry Canada Industrie Canada **ICES-003**
- **FC** PART 15