

# TS-B950

## RED LIGHT CONTROL/MONITORING SYSTEM



### FEATURES

- Beacon and steady burning obstruction light control
- Very stable under voltage variations
- "0" voltage switching reduces noise and preserves bulb life (2 to 3 times longer lamp life)
- Heatsink mounted outside the enclosure for proper heat dissipation
- Automatic photo control
- Extremely reliable
- Transfer function: turns on only one bulb of a DOL fixture and transfers to the other bulb in case of a failure of the first one.
- 3 alarm contacts for remote diagnostics of lamps and controller

### SPECIFICATIONS

#### Monitoring

Lamp type	LED or incandescent.
-----------	----------------------

#### Electrical value

Power consumption	5 Watts
-------------------	---------

Power requirements	120 Vac 50/60hz also available in 240 Vac or 24 Vdc
--------------------	--

#### Mechanical

Weight	3,6 Kg (8 lbs.)
--------	-----------------

Dimensions (W x H x D)	241 mm x 292 mm x 140 mm (9½" x 11½" x 5½")
------------------------	--

Enclosure material	Fiberglass
--------------------	------------





#### Others

Enclosure rating	Nema 1
------------------	--------

Operating temperature	-40°C to 55°C (-40°F to 131°F)
-----------------------	-----------------------------------

Warranty	2 years
----------	---------

### COMPLIANT WITH:

-  SPE-1000
-  Transports Canada Transport Canada CAR 621.19
-  Industrie Canada Industrie Canada ICES-003
-  PART 15